



**NON-POLAR ELECTROLYTIC CAPACITORS**



Highest quality. D.F. 7% or less.

Part#	MFD	Volts	4W Load	8W Load
2061	1	50	N/A	N/A
2062	2.2	50	N/A	N/A
2063	3.3	50	12KHz	12KHz
2064	4.7	50	8.5KHz	8.5KHz
2065	6.8	50	6KHz	6KHz
2066	15	50	2.5KHz	2.5KHz
2067	1.5	100	N/A	N/A
2068	7.8	100	5.1KHz	5.1KHz
2069	15	100	3.2KHz	3.2KHz
2092	22	100	1.8KHz	1.8KHz
2093	33	100	1.2KHz	1.2KHz
2094	47	100	800Hz	800Hz
2095	100	100	400Hz	400Hz
20952	200	100	200Hz	200Hz
20953	300	100	150Hz	150Hz
20954	400	100	100Hz	100Hz
20955	500	100	80Hz	80Hz
20956	600	100	65Hz	65Hz

**LATCH CIRCUIT**



Highest quality. D.F. 7% or less.

Part#	MFD	Volts	4W Load	8W Load
2071	1.0	100	N/A	N/A
2071	1.5	100	N/A	12KHz
20719	2.2	100	N/A	12KHz
2072	3.3	100	12KHz	6KHz
20724	4.0	100	10KHz	5KHz
20725	5.0	100	8KHz	4KHz
2090	6.8	100	6KHz	3KHz
20718	8.0	100	5KHz	2.5KHz
2091	10.0	100	4KHz	2KHz

**CARBON FILM RESISTORS**



Qty's 100, 500 & 1000 1/4 Watt.

**RESISTOR COLOR CODE**

Color	Digit	Multi	%
Black	0	0	0
Brown	1	10	10
Red	2	10 <sup>2</sup>	0.1
Orange	3	10 <sup>3</sup>	0.01
Yellow	4	10 <sup>4</sup>	0.001
Green	5	10 <sup>5</sup>	-
Blue	6	10 <sup>6</sup>	-
Violet	7	-	-
Grey	8	-	-
White	9	-	-

TECH TIP: Use in series with LEDs lower values used with self-flashing LEDs.

**POWER DIODES**



Qty's 20, 50, & 100

Part#	Type
5501	1 Amp
5503	3 Amp
5506	6 Amp


**AIR CORE INDUCTORS**



For tweeters and mids

Part#	mH	Gauge	4W Load	8W Load
L260	.6	22	1.1KHz	2.2KHz
L280	.8	22	800Hz	1.6KHz
LA648	6.4	18	100Hz	200Hz
LA646	6.4	16	100Hz	200Hz

**LAMINATED "I" CORE INDUCTORS**



MH Coils. For mid bass, bass. Recommended for 250-300 Watts

Part#	mH	Gauge	4W Load	8W Load
L60	60	18	1.1KHz	2.4KHz
L25	2.5	18	250Hz	500KHz

**AXIAL WIRE WOUND RESISTORS**



TECH TIP:

1) 10 ohm 10W used for ignition kills. Ground one side of resistor through a switch, the other (-) side of coil.

2) Use in series with low power factory car speakers to lower power delivered to them for blow out protection or balancing without the loss of full range sound or when crossover is not appropriate


Part#	OHM
2096	1.5
2097	2.2
2098	3.3
2099	4.7
3000	5.5
3001	8.0
3002	10.0
3003	15.0
3004	20.0
3005	33.0
3006	50.0

**ABS PLASTIC PLEXIGLASS/BLACK VINYL STEEL**



Part#	Type	Description	Thickness	Size
50966	Steel	Black Vinyl	1/16"	12 x 6"
5097	ABS	Textured Black	1/8"	12 x 4"
5096	ABS	Textured Black	1/8"	12 x 12"
509622	ABS	Textured Black	1/8"	22 x 9"
5099	ABS	Textured Black	1/8"	24 x 24"
5097 Thin	ABS	Textured Black	3/32"	12 x 4"
5096 Thin	ABS	Textured Black	3/32"	12 x 12"
5099 Thin	ABS	Textured Black	3/32"	24 x 24"
5096 Grid	ABS	Black Grid Waffle Board	3/32"	12 x 12"
PLX CL	Plexy	Clear (see-thru)	1/8"	24 x 24"
PLX TN	Plexy	Tinted (see-thru)	1/8"	24 x 24"
PLX BK	Plexy	Black Glossy	1/8"	24 x 24"
PLX WH	Plexy	White Glossy	1/8"	24 x 24"
PLX BR	Plexy	Brown Glossy	1/8"	24 x 24"
PLX RD	Plexy	Red Glossy	1/8"	24 x 24"
PLX BL	Plexy	Blue Glossy	1/8"	24 x 24"

**BLACK WIRE MESH SCREENS**



New 12" and 18" wide wire mesh screen perfect for custom grills or speaker protections

Part#	Size
WM12	12"
WM18	18"

**PLEXY EDGE FINISH/POLISH**



Removes fine scratches, haziness and abrasions for plexy glass surfaces. Restores faded and discolored plastics

Part#
4621

**PLEXIGLASS GLUE**



Especially formulated for affixing plexiglass and other plastics (i.e. ABS hinge to plexy)

Part#	Size
6172Q	Pint

**ACCELE® SCREW-N-SNAP™**



Round screw mountable snaps. Ideal for custom panel mounts, cellular phones, amps, distribution blocks, etc. Easy on and off with the clean screwless look. Sold 12 to a pack.

Part#
2054

